



www.wearwell.com

Rejuvenator Squared Flooring

Group 502-F

Rejuvenator Flooring features large 3'x3' (91 cm x 91 cm) and 1'x3' (30 cm x 91 cm) tiles that interlock on all 4 sides to customize on-site virtually any flooring configuration. The interlock is incredibly effective--and also hidden--so the ergonomic floor you've created is seamless and stable underfoot. Having the ability to customize in 1 foot (30 cm) increments and finish off with beveled ramps [yellow or black] sets Rejuvenator Flooring apart from all other urethane "wannabees".

- Configure large areas quickly
- Deep Positive Lock keeps seams secure
- 100% Urethane with thick outer wear layer
- Meets USP 797 compliance standards
- Customizable in 1' (30 cm) increments
- Overall thickness 5/8" (16 mm)

Type	Anti-Fatigue Flooring
Suitable Environment	Dry
Customization Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Compound	Polyurethane
Recycled	<10%
Warranty	Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1% lost @ 1,000 cycles
Temperature Range	-50 to 250 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .75 / Wet: COF = .28
Compression Deflection	ASTM D 395 / 30 minutes 5.67 / 24 hours 1.42
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

Part Number	UPC	Color	Thickness	Dimensions	Stock Part	UOM
502.58x1x3BK	715411004584	Black		1' x 3'	Y	EA
502.58X3X3BK	715411284306	Black	0.625	3' x 3'	Y	EA